



Dewpoint Art. Nr. 5020-0560 06.04.2005

## Combination instrument for temperature, humidity and dewpoint

### Dewpoint Pro



- Very fast capacity humidity sensor from the switzerland
- Indicates dewpoint and wetbulb
- 1- second measuring interval
- MAX-MIN-HOLD-Function
- C/F-switchable
- Switchable Auto-off-function

#### Applications

Compact thermohygrometer with a lot of features, perfect for measuring ambient conditions: HVAC, food storage, buildings, offices, production plants. Easy to use: For detecting critical temperature-humidity environments, e.g.: mould in living quarters.

- § Building industry
- § HVAC
- § Education
- § Laboratory
- § Food (process & storage)



Incl. stand

#### Technical data

##### Temperature

Measuring range -40..+70°C  
 Display resolution 0,1°C  
 Accuracy ± 0,5°C

##### Humidity

Measuring range 0..99%rF  
 Display resolution 0,1%  
 Accuracy ± 3%(20..80%) remaining range ± 4%

Working temperature -40..70°C  
 Battery life time Typical 1000 hours by continously use  
 Battery 2 x 1,5 Volt AAA size  
 Dimensions 170 x 50 x 17 mm  
 Weight 100gr. (incl. packaging)

Functions: Max/Min/Hold-Function, dewpoint, wetbulb, calibration certificate as an option  
 C/F-switchable